

SCD

4.5Ø x 14.5 mm

Time-Lag Fuse



Agency Approvals

Agency	Ampere Rating
Certified products for U.S. and Canada	100mA - 8A

Interrupting Rating

1A - 8A:	10,000 amperes at 125V AC
1A - 8A:	200 amperes at 250V AC
1A - 8A:	100 amperes at 350V AC

Product Characteristics

Operating Temperature	-55 °C to 125 °C
Material	Body: Ceramic / Caps: Nickel Plated Brass


Electrical Characteristics

Ampere Rating	Opening Time			
	1 In		2 In	
	MIN	MAX	MIN	MAX
1A - 8A	4 hr	1 hr	2 sec	120 sec

Packaging

Packaging Option	Quantity
Bulk	2,000 pcs / box

Mechanical Dimensions (mm)



SCD-A

4.5Ø x 14.5 mm

Time-Lag Fuse



Agency Approvals

Agency	Ampere Rating
Certified products for U.S. and Canada	100mA - 8A

Interrupting Rating

1A - 8A:	10,000 amperes at 125V AC
1A - 8A:	200 amperes at 250V AC
1A - 8A:	100 amperes at 350V AC

Product Characteristics

Operating Temperature	-55 °C to 125 °C
Material	Body: Ceramic / Caps: Nickel Plated Brass
Leads Wire	Ø0.63 mm 7A and less. Ø1.0 mm for rating above 8A.

Electrical Characteristics

Ampere Rating	Opening Time			
	1 In		2 In	
	MIN	MAX	MIN	MAX
1A - 8A	4 hr	1 hr	2 sec	120 sec

Packaging

Packaging Option	Quantity
Bulk	500 pcs / box
On Axial Tape & Reel	1,000 pcs / box

Mechanical Dimensions (mm)

