

JNR13S series							
Diameter	Model No.	Resistance at 25°C (Ω)	Thermal dissipation coefficient (mW/°C)	Thermal Time constant (S)	I _{max} (A)	Maximum Capacitance AC240V (uF)	Rated Temperature TL~TU(°C)
13D	13S1R0M	1	≥13	≤130	7.0	330	-40~+200
	13S1R0L	1			7.0		
	13S1R3M	1.3			7.0		
	13S1R3L	1.3			7.0		
	13S2R0M	2			5.0		
	13S2R0L	2			5.0		
	13S2R5M	2.5			6.0		
	13S2R5L	2.5			6.0		
	13S030M	3			6.0		
	13S030L	3.0			6.0		
	13S040M	4			5.0		
	13S040L	4			5.0		
	13S4R7M	4.7			5.0		
	13S4R7L	4.7			5.0		
	13S050M	5			5.0		
	13S050L	5.0			5.0		
	13S060L	6			5.0		
	13S070L	7			4.0		
	13S080L	8			4.0		
	13S100L	10			5.0		
	13S120L	12			4.0	560	
	13S150L	15			3.0		
	13S160L	16			3.0		
13S180L	18	3.0	470				
13S200L	20	2.8					
13S250L	25.0	2.0	560				

13S500L	50.0		2.0	560
---------	------	--	-----	-----